



■ **Parallel connector, copper 1.5 - 300 mm²**
standard type



- For connecting different cable cross-sections

Characteristics


- Annealed material optimises material and crimping characteristics

Material

- Copper to EN 13600



Surface

- Tin plated



Total cross-section mm ²	Part No.	Dimensions mm			Weight/100 pcs. ~ kg	pcs.
		d1	d4	l		
1.5	148R	1.8	3.3	5	0.03	100
2.5	149R	2.3	4.2	5	0.04	100
4	150R	3.0	5.0	7	0.08	100
6	151R	4.0	6.0	7	0.09	100
10	152R	4.5	7.0	9	0.17	100
16	153R	5.5	8.5	10	0.28	100
25	154R	7.0	10.0	13	0.44	100
35	155R	8.5	12.0	16	0.78	100
50	156R	10.0	14.0	19	1.22	100
70	157R	12.0	16.5	19	1.62	50
95	158R	13.5	18.0	20	1.90	50
120	159R	15.0	19.5	22	2.28	50
150	160R	16.5	21.0	26	3.00	50
185	161R	19.0	24.0	30	4.37	50
240	162R	21.0	26.0	32	5.30	25
300	163R	23.5	29.5	36	8.05	25

► Tool: see chart page 44



T-connectors, copper 1.5 - 240 mm²
standard type

- For single cable tap conductors
- For stranded conductors e.g. VDE 0295 Class 2

Characteristics


- Annealed material optimises material and crimping characteristics

Material

- Copper to EN 13600

Surface



- Tin plated



Cross-section mm ²	Part No.	Dimensions mm				Weight/100 pcs. ~ kg	pcs.
		d1	d4	l	l1		
1.5	TV15	1.8	3.3	30	12	0.23	50
2.5	TV2.5	2.3	4.2	30	12	0.37	50
4	TV4	3.0	5.0	30	12	0.45	50
6	TV6	4.0	6.0	35	14	0.73	50
10	TV10	4.5	7.0	35	14	1.05	50
16	TV16	5.5	8.5	50	21	2.20	50
25	TV25	7.0	10.0	55	23	2.90	25
35	TV35	8.5	12.0	70	30	5.20	25
50	TV50	10.0	14.0	80	34	7.90	25
70	TV70	12.0	16.5	85	35	11.20	10
95	TV95	13.5	18.0	90	36	13.00	10
120	TV120	15.0	19.5	95	38	14.70	10
150	TV150	16.5	21.0	110	44	18.90	10
185	TV185	19.0	24.0	115	45	25.00	5
240	TV240	21.0	26.0	130	52	31.10	5

▶ Tool: see chart page 44

■ **Cross-connector, copper 1.5 - 240 mm²**
standard type



- For double cable tap conductors
- For stranded conductors e.g. VDE 0295 Class 2

Characteristics


- Annealed material optimises material and crimping characteristics

Material

- Copper to EN 13600

Surface

- Tin plated



Cross-section mm ²	Part No.	Dimensions mm				Weight/100 pcs. ~ kg	pcs.
		d1	d4	l	l1		
1.5	KV15	1.8	3.3	30	12	0.320	25
2.5	KV2.5	2.3	4.2	30	12	0.490	25
4	KV4	3.0	5.0	30	12	0.650	25
6	KV6	4.0	6.0	35	14	0.950	25
10	KV10	4.5	7.0	35	14	1.350	25
16	KV16	5.5	8.5	50	21	2.950	25
25	KV25	7.0	10.0	55	23	4.000	15
35	KV35	8.5	12.0	70	30	6.900	15
50	KV50	10.0	14.0	80	34	10.400	15
70	KV70	12.0	16.5	85	35	14.600	15
95	KV95	13.5	18.0	90	36	17.100	15
120	KV120	15.0	19.5	95	38	19.400	5
150	KV150	16.5	21.0	110	44	24.100	5
185	KV185	19.0	24.0	115	45	32.100	5
240	KV240	21.0	26.0	130	52	41.100	5

► Tool: see chart page 44