


■ **Solderless connector to DIN, copper, 0.5 - 150 mm²**



- For connecting different conductor cross-sections
- short standard type

Characteristics


- Manufactured according to DIN 46341, part 1, form A
- short standard type

Material

- Copper to EN 13 600


Surface

- tin plated



| Cross-section mm ² | Nominal size to DIN | Part No. | Dimensions mm | | | Weight/ 100 pcs. ~ kg | pcs. |
|-------------------------------|---------------------|--------------|---------------|------|----|-----------------------|------|
| | | | d1 | d4 | l | | |
| 0.5 - 1 | 1 | 1620K | 1.6 | 3.2 | 8 | 0.045 | 100 |
| 1.5 - 2.5 | 2.5 | 1630K | 2.3 | 3.9 | 8 | 0.055 | 100 |
| 4 - 6 | 6 | 1650K | 3.6 | 5.6 | 9 | 0.090 | 100 |
| 10 | 10 | 1652K | 4.5 | 6.7 | 10 | 0.170 | 100 |
| 16 | 16 | 1653K | 5.8 | 8.2 | 11 | 0.260 | 100 |
| 25 | 25 | 1654K | 7.5 | 10.5 | 14 | 0.510 | 100 |
| 35 | 35 | 1655K | 9.0 | 12.2 | 16 | 0.730 | 100 |
| 50 | 50 | 1656K | 11.0 | 14.6 | 19 | 1.200 | 100 |
| 70 | 70 | 1657K | 13.0 | 17.0 | 19 | 1.530 | 50 |
| 95 | 95 | 1658K | 15.0 | 20.0 | 20 | 2.370 | 50 |
| 120 | 120 | 1659K | 16.5 | 22.5 | 22 | 3.450 | 50 |
| 150 | 150 | 1660K | 19.0 | 25.4 | 26 | 5.060 | 50 |

► Tool: see chart page 87



■ Solderless connector to DIN, copper, 0.5 - 150 mm²

- For conductors, e.g. VDE 0295 Class 2, 5 and 6
- With buttmarks for precise cable insertion

Characteristics


- Manufactured according to DIN 46341, part 1, form B
- long standard type

Material

- Copper to EN 13 600

Surface

- tin plated



| Cross-section mm ² | Nominal size to DIN | Part No. | Dimensions mm | | | Weight/100 pcs. ~ kg | pcs. |
|-------------------------------|---------------------|--------------|---------------|------|----|----------------------|------|
| | | | d1 | d4 | l | | |
| 0.5 - 1 | 1 | 1620L | 1.6 | 3.2 | 15 | 0.08 | 100 |
| 1.5 - 2.5 | 2.5 | 1630L | 2.3 | 3.9 | 15 | 0.10 | 100 |
| 4 - 6 | 6 | 1650L | 3.6 | 5.6 | 15 | 0.19 | 100 |
| 10 | 10 | 1652L | 4.5 | 6.7 | 21 | 0.36 | 100 |
| 16 | 16 | 1653L | 5.8 | 8.2 | 26 | 0.62 | 100 |
| 25 | 25 | 1654L | 7.5 | 10.5 | 29 | 1.11 | 100 |
| 35 | 35 | 1655L | 9.0 | 12.2 | 32 | 1.50 | 100 |
| 50 | 50 | 1656L | 11.0 | 14.6 | 38 | 2.44 | 100 |
| 70 | 70 | 1657L | 13.0 | 17.0 | 42 | 3.54 | 50 |
| 95 | 95 | 1658L | 15.0 | 20.0 | 48 | 5.87 | 50 |
| 120 | 120 | 1659L | 16.5 | 22.5 | 52 | 8.46 | 50 |
| 150 | 150 | 1660L | 19.0 | 25.4 | 56 | 10.86 | 50 |

► Tool: see chart page 87