

■ **Parallel groove clamps, Cu 2.5 - 95 mm<sup>2</sup>**

- For screwing conductors to VDE 0295 Class 1 and 2, for example in lighting protection areas

**Characteristics**


- For outdoor assembly
- Version with 1 screw
- Without thrust plate

**Material**

- Cu-ETP
- Screw: high tensile copper alloy F 60
- Nut: Copper

**Surface**

- bright



Cross-section mm <sup>2</sup>	Part No.	Dimensions mm				Weight/100 pcs. ~ kg	pcs.
		b	h	l	M		
2,5 - 16	<b>SAK10</b>	19.5	16	16	M5	2.10	10
2,5 - 25	<b>SAK12</b>	25.0	21	18	M6	4.10	10
	<b>SAK14</b>	25.0	22	18	M7	3.95	10
6 - 35	<b>SAK16</b>	28,0	23	20	M7	6,0	10
6 - 50	<b>SAK18</b>	32.5	26	20	M7	8,0	10
	<b>SAK20</b>	33,5	27	22	M8	8,6	10
6 - 70	<b>SAK22</b>	37,5	29	24	M8	11,1	5
10 - 95	<b>SAK24</b>	41,0	36	28	M8	15,6	5

■ **Parallel groove clamps, Cu 2.5 - 95 mm<sup>2</sup>**

- For screwing conductors to VDE 0295 Class 1 and 2, for example in lighting protection areas

**Characteristics**



- For outdoor assembly
- Version with 1 screw
- With thrust plate

**Material**

- Cu-ETP
- Screw: high tensile copper alloy F 60
- Nut: Copper

**Surface**


- bright



Cross-section mm <sup>2</sup>	Part No.	Dimensions mm				Weight/100 pcs. ~ kg	pcs.
		b	h	l	M		
2,5 - 16	<b>SAK11</b>	19.5	16	16	M5	2,6	10
2,5 - 25	<b>SAK13</b>	25.0	21	18	M6	4.30	10
	<b>SAK15</b>	25.0	22	18	M7	4,6	10
6 - 35	<b>SAK17</b>	28,0	23	20	M7	6,3	10
6 - 50	<b>SAK19</b>	32.5	26	20	M7	7,9	10
	<b>SAK21</b>	33,5	27	22	M8	9,1	10

■ Parallel groove clamps, Cu 2.5 - 95 mm<sup>2</sup>

Cross-section mm <sup>2</sup>	Part No.	Dimensions mm				Weight/100 pcs. ~ kg	pcs.
		b	h	l	M		
6 - 70	<b>SAK23</b>	37	29	24	M8	11,6	5
10 - 95	<b>SAK25</b>	45	36	31	M10	19.6	5



■ Parallel groove clamps, Cu 2.5 - 150 mm<sup>2</sup>

- For screwing conductors to VDE 0295 Class 1 and 2, for example in lighting protection areas

**Characteristics**

- For outdoor assembly
- Version with 2 screws
- Without thrust plate

**Material**

- Cu-ETP
- Screw: high tensile copper alloy F 60
- Nut: Copper

**Surface**

- bright

Cross-section mm <sup>2</sup>	Part No.	Dimensions mm					Weight/100 pcs. ~ kg	pcs.
		b	A	h	l	M		
2,5 - 16	<b>SAK30</b>	20,5	13,0	16	24	M5	3,7	10
2,5 - 25	<b>SAK32</b>	25,5	13,5	21	27	M6	6,4	10
	<b>SAK34</b>	25,0	15,0	22	30	M7	7,7	10
6 - 35	<b>SAK36</b>	30,0	15,0	23	30	M7	8,5	10
6 - 50	<b>SAK38</b>	33	16,0	26	32	M7	12,3	10
10 - 50	<b>SAK40</b>	32,5	18,0	27	36	M8	12,9	10
6 - 70	<b>SAK42</b>	37	19,0	29	38	M8	18,1	5
10 - 95	<b>SAK44</b>	45,0	25,5	36	46	M10	28,7	5
16 - 150	<b>SAK46</b>	52,5	26,0	40	52	M10	37,4	5