

■ **HS 2**

High-pressure hoses

Characteristics

- For hydraulic crimping/cutting systems and drive units
- For connecting to: FHP 2, PHD 1, EHP 2, EHP 3, EHP 5, HK 12/2 EL, HK 25/2 EL, K 502, K 202, K 303/1, K 303/2, K 404, HK 12/2, HK25/2, HK 45

Item	Part No.
High-pressure hose, 2m	HS22
High-pressure hose, 3m	HS23
High-pressure hose, 4m	HS24
High-pressure hose, 5m	HS25
High-pressure hose, 6m	HS26
High-pressure hose, 8m	HS28
High-pressure hose, 10m	HS210



■ **KST 2**

Coupler plug

Characteristics

- For hydraulic crimping/cutting systems and drive units
- Including adapter
- Suitable for high-pressure hoses HS2

Item	Part No.
Coupler plug	KST2





■ **KMF 1**
Coupling box

Characteristics

- For connecting to hydraulic crimping/cutting heads: PK 18, PK 22, PK 120/38, PK 120 U, PK 25/2, PK 45, PK 60 VP, PK 60 VP/FT, PK 60 UNV, SDG 45, SDG 50 and SDG 85
- For hydraulic systems: THK 18, THK 22, HK 12/2, HK 25/2, HK 45, HK 12/2 EL, HK 25/2 EL, K 303/1, K 303/2, K 404, SDK 502 and SDK 202
- Includes barrel nipple

Item	Part No.
Coupling box	KMF1



■ **KMF 2**
Coupling box

Characteristics

- For connecting to high-pressure hoses for hydraulic cutting tools: K 303/1, K 303/2, K 404
- Includes barrel nipple

Item	Part No.
Coupling box	KMF2

■ **DNP 2**

Barrel nipple

Characteristics

- For connecting resp. extending high-pressure hoses of series HS 2

Item	Part No.
Barrel nipple	DNP2



■ **TW 50**

Transport trolley

Characteristics

- For electro hydraulic drive units
- Weight: 10.9 kg

Item	Part No.
Transport trolley	TW50



■ **ZST 3**

Two hand safety control system

Characteristics

- For electro hydraulic drive units: EHP 2, EHP 3
- Connecting cable, 10 m



Item	Part No.
Two hand safety control system	ZST3

■ **FTA 1**

Safety foot switch

Characteristics

- For hydraulic drive units: EHP 2, EHP 3, HK 12/2 EL, HK 25/2 EL
- Connecting cable, 10 m



Item	Part No.
Foot switch	FTA1