



■ SDG 45

Hydraulic cutting head max. Ø 45 mm

- Extremely sturdy design
- Cuts armoured copper and aluminium cables and Al/St cables (ACSR)

Characteristics

- Closed head with bolt interlock, flip open jaws
- Cutting head with quick coupling , rotates 360°
- For connecting to hydraulic drive units with 700 bar operating pressure for the best possible cutting results



Technical Data	
Cutting range:	max. cable size = Ø 45 mm (dependant on cable type), e.g. Al/St cable 570/40
Operating pressure:	max. 700 bar
Length:	340 mm
Weight:	3.8 kg

Item	Part No.	Page
Hydraulic cutting head max. Ø 45 mm	SDG45	
Scope of supply	Part No.	Page
Carrying bag	TT2	

Accessories	Part No.	Page
Outer, stationary blade	ESG45EF	353
Inner, moving blade	ESG45ES1	353



■ **SDG 50**

Hydraulic cutting head max. Ø 50 mm

■ **Cuts copper and aluminium cables**

Characteristics

- Closed crimping head, flip top style
- Cutting head with quick coupling , rotates 360°
- For connecting to hydraulic drive units with 700 bar operating pressure for the best possible cutting results



Technical Data	
Cutting range:	max. cable size = Ø 50 mm (depending on cable type) e.g. 4 x 120 mm² NYY
Operating pressure:	max. 700 bar
Length:	330 mm
Weight:	2.5 kg

Item	Part No.
Hydraulic cutting head max. Ø 50 mm	SDG50
Scope of supply	Part No. Page
Carrying bag	TT2

Accessories	Part No.	Page
Outer, fixed blade	ESG50EF1	354
Inner, moving blade	ESG50ES	354





■ SDG 85

Hydraulic cutting head max. Ø 85 mm

■ Cuts copper and aluminium cables

Characteristics

- Sturdy cutting head in closed design
- Cutting head with quick coupling , rotates 360°
- For connecting to hydraulic drive units with 700 bar operating pressure for the best possible cutting results



Technical Data	
Cutting range:	max. cable size = Ø 85 mm (dependent on cable type), e.g. 4 x 240 mm ² NYN
Operating pressure:	max. 700 bar
Length:	420 mm
Weight:	6.1 kg

Item	Part No.	
Hydraulic cutting head max. Ø 85 mm	SDG85	
Scope of supply	Part No.	Page
Carrying bag	TT2	

Accessories	Part No.	Page
Outer, fixed blade	ESG85EF	354
Inner, moving blade	ESG85ES	354

■ SDK 502

Hydraulic cutting head max. Ø 50 mm

- **Extremely sturdy design**
- **Cuts copper and aluminium cables**

Characteristics

- Open cutting head with quick coupling , rotates 360°
- For connecting to hydraulic drive units with 700 bar operating pressure for the best possible cutting results



Technical Data	
Cutting range:	max. cable size = Ø 50 mm (depending on cable type)
Operating pressure:	max. 700 bar
Weight:	4.6 kg

Item	Part No.
Hydraulic cutting head max. Ø 50 mm	SDK502
Scope of supply	Part No. Page
Carrying bag	TT2





■ SDK 202

Hydraulic cutting heads

- Extremely sturdy design
- Cuts copper and aluminium cables

Characteristics

- Open cutting head with quick coupling , rotates 360°
- For connecting to hydraulic drive units with 700 bar operating pressure for the best possible cutting results



Technical Data		
	SDK 202/1	SDK 202/2
Cutting range:	max. Ø 90 mm	max. Ø 120 mm
Operating pressure:	max. 700 bar	700
Weight:	10.5 kg	12.5 kg

Item	Part No.	
Hydraulic cutting head max. Ø 90 mm	SDK2021	
Hydraulic cutting head max. Ø 120 mm	SDK2022	
Scope of supply	Part No.	Page
Carrying bag	TT4	