





■ Crimping dies HR 25

Suitable for:

- Copper tubular cable lugs and connectors, standard design
- Tubular cable lugs for switchgear connections





mm ²	Part No.	Crimp width mm	
16	HR2516	10	
25	HR2525	10	
35	HR2535	10	
50	HR2550	13	
70	HR2570	13	
95	HR2595	15	
120	HR25120	15	
150	HR25150	20	
185	HR25185	20	
240	HR25240	20	
300	HR25300	20	
400	HR25400	20	


■ Crimping dies HIS 25

Suitable for:

- Insulated tubular cable lugs and connectors
- Insulated pin terminals



mm ²	Part No.	Crimp width mm	
10	HIS2510	7	
16	HIS2516	7	
25	HIS2525	8	
35	HIS2535	8	
50	HIS2550	10	
70	HIS2570	12	
95	HIS2595	14	
120	HIS25120	14	
150	HIS25150	16	





■ Crimping dies HF 25

Suitable for:

- Tubular cable lugs and compression joints for fine stranded conductors

mm ²	Part No.		
16	HF2516		
25	HF2525		
35	HF2535		
50	HF2550		
70	HF2570		
95	HF2595		
120	HF25120		
150	HF25150		
185	HF25185		
240	HF25240		
300	HF25300		





■ Crimping dies HD 25

Suitable for:

- Copper compression cable lugs (DIN 46235) and connectors (DIN 46267, part 1) acc. to DIN

mm ²	Part No.	Code	Crimp width mm
16	HD2516	8	10
25	HD2525	10	10
35	HD2535	12	10
50	HD2550	14	13
70	HD2570	16	13
95	HD2595	18	14
120	HD25120	20	14
150	HD25150	22	15
185	HD25185	25	15
240	HD25240	28	15
300	HD25300	32	17
400	HD25400	38	17
500	HD25500	42	17
625	HD25625	44	15



■ Crimping dies HDP 25

Suitable for:


- Double compression cable lugs

mm ²	Part No.	Crimp width mm	
2 x 50	HDP2550	15	
2 x 70	HDP2570	15	
2 x 95	HDP2595	15	
2 x 120	HDP25120	15	

■ Crimping dies HQ 25

Suitable for:

- Copper solderless terminals (DIN 46234) and pin terminals (DIN 46230) acc. to DIN
- Copper solderless connectors (DIN 46341) acc. to DIN




mm ²	Part No.		
16	HQ2516		
25	HQ2525		
35	HQ2535		
50	HQ2550		
70	HQ2570		
95	HQ2595		
120	HQ25120		
150	HQ25150		
185	HQ25185		
240	HQ25240		

■ Crimping dies HISQ 25

Suitable for:

- Insulated solderless terminals and pin terminals





mm ²	Part No.		
10	HISQ2510		
16	HISQ2516		
25	HISQ2525		
35	HISQ2535		
50	HISQ2550		
70	HISQ2570		
95	HISQ2595		
120	HISQ25120		
150	HISQ25150		



■ Crimping dies HRU 25

Suitable for:

- Pre-rounding dies for sector-shaped Al and Cu conductors
- 3- and 4-core sector-shaped conductors



mm ² se	mm ² sm	Part No.	Conductor Ø mm	Pre-rounding width mm
	10	HRU2510	4.1	40
	16	HRU2516	5.1	40
35	25	HRU253525	6.3	40
50	35	HRU255035	7.5	40
70	50	HRU257050	9.0	40
95	70	HRU259570	10.5	40
120	95	HRU2512095	12.5	40
150	120	HRU25150120	14.0	40
185	150	HRU25185150	15.8	40
240	185	HRU25240185	17.5	40
300	240	HRU25300240	20.3	40
	300	HRU25300SM	22.5	40





■ Crimping dies HA 25

Suitable for:

- Aluminium compression cable lugs and connectors to DIN
- Aluminium/copper compression cable lugs and connectors acc. to DIN

mm ²	Part No.	Code	Crimp width mm
10	HA2510	10	12
16-25	HA251625	12	12
35	HA2535	14	12
50	HA2550	16	12
70	HA2570	18	12
95-120	HA2595120	22	14
150	HA25150	25	14
185	HA25185	28	14
240	HA25240	32	17
300	HA25300	34	17
400	HA25400	38	17
500	HA25500	44	15





■ Crimping dies HAD 25

Suitable for:

- Compression joints for full tension connections of Aldrey conductors acc. to DIN EN 50182
- Al-conductors acc. to DIN EN 50182, 120 – 300 mm²

mm ²	Part No.	Code	Crimp width mm
25	HAD2525	12	12
35	HAD2535	14	12
50	HAD2550	16	12
70	HAD2570	18	12
95	HAD2595	20	14
120	HAD25120	25	14
150-185	HAD25150185	28	14
240	HAD25240	34	17
300	HAD25300	38	17



■ Crimping dies HAST 25

Suitable for:



- Compression joints DIN 48085, part 3 - Al/St-cable DIN EN 50182
- Aluminium compression

mm ²	Part No.	Code	Crimp width mm
25-4	HAST2525	12	12
35-6	HAST2535	14	12
50-8	HAST2550	16	12
70-12	HAST2570	18	12
95-15	HAST2595	22	14
120-20	HAST25120	25	14

■ **Crimping dies HST 25**



Suitable for:

- Compression joints DIN 48085, part 3 - Al/St-cable DIN EN 50182
- Steel compression



mm ²	Part No.	Code	Crimp width mm
25-4 35-6	HST2546	6	14
50-8	HST258	7	14
70-12 95-15	HST251215	9	14
120-20	HST2520	13	14

■ **Crimping dies HAH 25**





Suitable for:

- Clamps, H-type

mm ²	Part No.	Crimp width mm	
70	HAH2570	20	
95	HAH2595	20	
120	HAH25120	20	



■ **Crimping dies HC 25 / HMC 25**



Suitable for:

- Clamps, C-type

mm ²	Part No.	Crimp width mm	
16	HC2516	16	
25	HC2525	17	
35	HC2535	20	
50	HC2550	20	
70	HC2570	20	
95	HC2595	20	
10-16 10-25 35-35	HMC2535	18	
25-50 50-50	HMC2550	20	
35-70	HMC2570	20	
35-95 70-95	HMC2595	20	
120-120	HMC25120	20	
150-150	HMC25150	20	
185-185	HMC25185	20	




■ Crimping dies HAE 25

Suitable for:

- Cable end-sleeves

mm ²	Part No.	Crimp width mm	
25	HAE2525	20	
35	HAE2535	20	
50	HAE2550	26	
70	HAE2570	26	
95	HAE2595	26	
120	HAE25120	26	
150	HAE25150	26	
185	HAE25185	26	
240	HAE25240	26	



■ Crimping dies HAES 25

Suitable for:

- Cable end-sleeves
- Special trapezoid crimps for „compacted“ fine stranded conductors

mm ²	Part No.	Crimp width mm	
25	HAES2525	20	
35	HAES2535	20	
50	HAES2550	26	
70	HAES2570	26	
95	HAES2595	26	
120	HAES25120	26	
150	HAES25150	26	
185	HAES25185	26	
240	HAES25240	26	