

■ **Pulling grips Junior, closed**

Suitable for:


- For pulling cables with small diameters
- For manual pulling of supply lines in pipes and cable ducts

Characteristics

- Single weave galvanized steel mesh with flexible pulling eye



Item	Part No.	Length of meshwork mm	Lug length mm	Max. pulling force kN
Pulling grips, Junior, closed for cable diameters Ø 5 - 6 mm	50305964	110	83	0.3
Pulling grips, Junior, closed for cable diameters Ø 7 - 9 mm	50305840	110	83	0.4
Pulling grips, Junior, closed for cable diameters Ø 10 - 12 mm	50305867	180	96	0.8
Pulling grips, Junior, closed for cable diameters Ø 13 - 15 mm	50305883	220	110	1.1
Pulling grips, Junior, closed for cable diameters Ø 16 - 18 mm	50305905	255	130	1.7
Pulling grips, Junior, closed for cable diameters Ø 19 - 25 mm	50305921	255	146	2.4
Pulling grips, Junior, closed for cable diameters Ø 26 - 31 mm	50305948	300	165	3.4



Pulling grips

■ T-Basket type pulling grips, closed

Suitable for:

- Medium duty type of pulls in pipes and ducts

Characteristics

- Double weave galvanized steel mesh with flexible pulling eye



Item	Part No.	Length of meshwork mm	Lug length mm	Max. pulling force kN
T-Basket type pulling grips closed for cable diameters Ø 13 - 15 mm	50305581	535	200	4.0
T-Basket type pulling grips closed for cable diameters Ø 16 - 18 mm	50305603	610	200	4.9
T-Basket type pulling grips closed for cable diameters 19 - 25 mm	50305620	610	230	6.0
T-Basket type pulling grips closed for cable diameters 26 - 38 mm	50305646	610	230	8.7
T-Basket type pulling grips closed for cable diameters 39 - 50 mm	50305662	610	280	14.5
T-Basket type pulling grips closed for cable diameters 51 - 63 mm	50305689	610	300	16.4
T-Basket type pulling grips closed for cable diameters 64 - 76 mm	50305700	610	300	21.7
T-Basket type pulling grips closed for cable diameters 77 - 88 mm	50305727	610	360	21.7
T-Basket type pulling grips closed for cable diameters 89 - 100 mm	50305743	660	360	27.5
T-Basket type pulling grips closed for cable diameters 19 - 25 mm	50305760	915	230	6.0
T-Basket type pulling grips closed for cable diameters 26 - 38 mm	50305786	915	230	8.7
T-Basket type pulling grips closed for cable diameters 39 - 50 mm	50310100	915	280	14.5
T-Basket type pulling grips closed for cable diameters 51 - 63 mm	50305808	915	300	16.4
T-Basket type pulling grips closed for cable diameters 64 - 76 mm	50310127	915	300	21.7
T-Basket type pulling grips closed for cable diameters 77 - 88 mm	50305824	915	360	21.7
T-Basket type pulling grips closed for cable diameters 89 - 100 mm	50310143	1020	360	27.5

■ Pulling grip set

Characteristics

- Set of the most important pulling grips for the most frequently required pulling operations

Item	Diameter mm	Part No.
Pulling grip set 50305840, 50305876, 50305883, 50305905, 50305921, 50305948	7-31 mm	50307584
Cable grip set 50305760, 50310100, 50305786	19-50 mm	50314823
Pulling grip set 50305808, 50310100, 50310127	51-76 mm	50314831
Pulling grip set 50305760, 50305786, 50305808, 50310100, 50310127	19-76 mm	50314840




■ Pulling grip open

- Easy and straight pulls when the end of the conductor is not available

Characteristics

- Single woven galvanised steel netting mesh with bar closure
- Offset flexible eye



Item	Part No.	Length of meshwork mm	Lug length mm	Max. pulling force kN
Pulling grip open, for cable diameters 13 - 15 mm	50306588	150	175	1.3
Pulling grip open, for cable diameters 16 - 18 mm	50310240	200	175	1.6
Pulling grip open, for cable diameters 19 - 25 mm	50306600	250	175	1.9
Pulling grip open, for cable diameters 26 - 31 mm	50310267	300	200	3.0
Pulling grip open, for cable diameters 32 - 38 mm	50306626	350	200	4.0
Pulling grip open, for cable diameters 39 - 44 mm	50310283	380	230	5.1
Pulling grip open, for cable diameters 45 - 50 mm	50306642	400	250	6.7
Pulling grip open, for cable diameters 51 - 63 mm	50310305	480	250	8.0
Pulling grip open, for cable diameters 64 - 76 mm	50306669	500	250	9.7
Pulling grip open, for cable diameters 77 - 88 mm	50310321	530	300	10.6
Pulling grip open, for cable diameters 89 - 100 mm	50306685	600	300	10.6